



High Image Quality

MATRIX III

The Eye II series are embedded with IRay independently developed high performance VOx detector which allows you to get high detailed thermal images, it will be much simpler to search targets in darkness. The Eye II series has excellent performance in critical temperature range. Matched with Matrix III™ powerful algorithm, it can improve the image contrast automatically, highlight the target and strengthen the image hierarchy, to make the imaging effect better, and find target faster.




HD Micro Display

1280X960 high resolution internal display offers crisp image and vivid colors.

High Resolution

Two kinds of detector resolutions available for options: 384x288 & 640x512.



Eye II Series

Bigger display and multifunctional operations enhance and record the excellent moment of your outdoor activities.

Big and Bigger.

E3PLUS / E3MAX / E6+ / E6PRO

Components controls



Built-in Video Recorder and WiFi Connection

The monocular has 8GB build-in memory to store the captured still images and video recording and WiFi module which allows 4 connections simultaneously.




High Image Frequency

50Hz

The 50Hz refresh rate guarantees you to capture every moment that you are interested.

14x Magnification


Up to 14-time magnification to identify the target easier.



Stadiametric Rangefinder

Based on estimated heights of targets user can get the rough distance from the target with the built-in stadiametric rangefinder fast and easy.


Picture-in-Picture Function



Picture-in-Picture improves accuracy by providing a 2x magnified image of the reticle area at the top of the display. It helps to zoom in on a target while retaining the rest of the field of view visible.


Hot Target Tracking

Track the hottest spot in the scene automatically and discover the target quickly.



5 Color Palettes

The Eye II series provides more than 5 color palettes for true colorized temperature mapping, including "white hot" "black hot" "red hot" "color" and "hot target highlight". Transitioning between different color palettes is fast and easy.



Model	E3Plus	E3Max	E6+	E6Pro
Detector Resolution, pixels	384x288	384x288	640x512	640x512
Pixel Size, μm	17	17	17	17
NETD, mK	≤ 50	≤ 50	≤ 50	≤ 50
Frame Rate, Hz	50	50	50	50
Objective Lens, mm	25	35	35	50
Field of View	$14.9^\circ \times 11.2^\circ$	$10.7^\circ \times 8^\circ$	$17.7^\circ \times 13.3^\circ$	$12.4^\circ \times 9.3^\circ$
Display Resolution, pixels	1280x960	1280x960	1280x960	1280x960
E-zoom	x2/x4	x2/x4	x2/x4	x2/x4
Detection Range, m (Target size: 1.7m x 1.2m)	973	1361	1361	1945
Max. Battery Life, h (Power saving mode)	4.5	4.5	4	4
Dimension, mm	181x65x64	186x65x64	188x65x64	202x65x64
Weight, g	<450	<450	<450	<520